

Economically move loads from 1 to 14 tons



AeroGo Aero-Pallets are designed to operate for load capacities from 1-14 tons. They are ideal for any application moving heavy, bulky loads. Because their travel path can change in every direction, Aero-Pallets are especially popular in applications such as lean manufacturing, product testing, manufacturing and component assembly. Aero-Pallets can work alongside or replace forklifts, cranes and conveyors at a fraction of the cost. Aero-Pallets are constructed of aluminum decks over four or more air caster units. Guide wheels provide optimum load control. Optional handles, chocks, throttle controls, and no-load wheels are available.

Ideal for Manufacturing. The omnidirectional, self-loading Aero-Pallet does not require any permanent floor fixtures or rails. The travel path can change as necessary. Components can be floated to the side of an assembly line without slowing production.

Near Zero Vibrations or Emissions. Quiet operation with zero emissions and vibration-less movement. A proven effective handling method for moving calibrated equipment.

Each Aero-Pallet Includes:

- Four or six Aero-Casters
- Automatic flow control valves
- One pressure regulator with gauge
- One on/off ball valve



Aero-Pallet with optional J-handle

Advantages to Moving Heavy Loads with Air Caster Technology:

- Low profile
- Low friction – no floor damage
- Economical and reliable
- Flexible for a variety of applications
- Easy omnidirectional multi-positioning
- Precise positioning without floor damage compared to traditional material handling equipment methods
- Ergonomic – reduces lift hazards
- Utilizes existing shop air
- Aero-Casters meet ASME specifications

Standard Specifications

| Capacity (lbs) | Model Number | Deck Size Area* (sq ft) | | Fixed Mount | | Net Wt. (lbs) | Air Flow** (SCFM) |
|-------------------|-----------------|-------------------------|-----|-------------|-----------|------------------|----------------------|
| | | Min | Max | Height (in) | Lift (in) | | |
| 4,000 | 4P8 --- | 2 | 5 | 1-7/8 | 3/8 | 55 | 32 |
| 4,000 | 4P8 --- | 5.1 | 10 | 1-7/8 | 3/8 | 85 | 32 |
| 4,000 | 4P8 --- | 10.1 | 15 | 1-7/8 | 3/8 | 115 | 32 |
| 10,000 | 4P12 --- | 4 | 10 | 1-7/8 | 3/4 | 85 | 56 |
| 10,000 | 4P12 --- | 10.1 | 15 | 1-7/8 | 3/4 | 115 | 56 |
| 10,000 | 4P12 --- | 15.1 | 20 | 1-7/8 | 3/4 | 145 | 56 |
| 10,000 | 4P12 --- | 20.1 | 25 | 1-7/8 | 3/4 | 175 | 56 |
| 15,000 | 6P12 --- | 25 | 30 | 1-7/8 | 3/4 | 210 | 84 |
| 15,000 | 6P12 --- | 30.1 | 35 | 1-7/8 | 3/4 | 240 | 84 |
| 15,000 | 6P12 --- | 35.1 | 40 | 1-7/8 | 3/4 | 270 | 84 |
| 15,000 | 6P12 --- | 40.1 | 45 | 1-7/8 | 3/4 | 300 | 84 |
| 17,000 | 4P15 --- | 7 | 10 | 1-7/8 | 7/8 | 90 | 56 |
| 17,000 | 4P15 --- | 10.1 | 15 | 1-7/8 | 7/8 | 120 | 56 |
| 17,000 | 4P15 --- | 15.1 | 20 | 1-7/8 | 7/8 | 150 | 56 |
| 17,000 | 4P15 --- | 20.1 | 25 | 1-7/8 | 7/8 | 180 | 56 |
| 25,500 | 6P15 --- | 25 | 30 | 1-7/8 | 7/8 | 215 | 84 |
| 25,500 | 6P15 --- | 30.1 | 35 | 1-7/8 | 7/8 | 255 | 84 |
| 25,500 | 6P15 --- | 35.1 | 40 | 1-7/8 | 7/8 | 275 | 84 |
| 25,500 | 6P15 --- | 40.1 | 45 | 1-7/8 | 7/8 | 305 | 84 |
| 28,000 | 4P21 --- | 13 | 15 | 2 | 1-1/8 | 130 | 48 |
| 28,000 | 4P21 --- | 15.1 | 20 | 2 | 1-1/8 | 160 | 48 |
| 28,000 | 4P21 --- | 20.1 | 25 | 2 | 1-1/8 | 190 | 48 |

Metric Specifications

| Capacity (kg) | Model Number | Deck Size Area* (m ²) | | Fixed Mount | | Net Wt. (kg) | Air Flow** (L/sec) |
|------------------|-----------------|-----------------------------------|------|-------------|-----------|-----------------|-----------------------|
| | | Min | Max | Height (mm) | Lift (mm) | | |
| 1,816 | 4P8 --- | 0.19 | 0.46 | 48 | 10 | 25 | 15 |
| 1,816 | 4P8 --- | 0.47 | 0.93 | 48 | 10 | 39 | 15 |
| 1,816 | 4P8 --- | 0.94 | 1.39 | 48 | 10 | 52 | 15 |
| 4,536 | 4P12 --- | 0.37 | 0.93 | 48 | 19 | 39 | 26 |
| 4,536 | 4P12 --- | 0.94 | 1.39 | 48 | 19 | 52 | 26 |
| 4,536 | 4P12 --- | 1.40 | 1.86 | 48 | 19 | 66 | 26 |
| 4,536 | 4P12 --- | 1.87 | 2.32 | 48 | 19 | 79 | 26 |
| 6,804 | 6P12 --- | 2.32 | 2.79 | 48 | 19 | 95 | 40 |
| 6,804 | 6P12 --- | 2.80 | 3.25 | 48 | 19 | 109 | 40 |
| 6,804 | 6P12 --- | 3.26 | 3.72 | 48 | 19 | 122 | 40 |
| 6,804 | 6P12 --- | 3.73 | 4.18 | 48 | 19 | 136 | 40 |
| 7,708 | 4P15 --- | 0.65 | 0.93 | 48 | 22 | 41 | 26 |
| 7,708 | 4P15 --- | 0.94 | 1.39 | 48 | 22 | 54 | 26 |
| 7,708 | 4P15 --- | 1.40 | 1.86 | 48 | 22 | 68 | 26 |
| 7,708 | 4P15 --- | 1.87 | 2.32 | 48 | 22 | 82 | 26 |
| 11,562 | 6P15 --- | 2.32 | 2.79 | 48 | 22 | 98 | 40 |
| 11,562 | 6P15 --- | 2.80 | 3.25 | 48 | 22 | 116 | 40 |
| 11,562 | 6P15 --- | 3.26 | 3.72 | 48 | 22 | 125 | 40 |
| 11,562 | 6P15 --- | 3.73 | 4.18 | 48 | 22 | 138 | 40 |
| 12,700 | 4P21 --- | 1.21 | 1.39 | 51 | 29 | 59 | 23 |
| 12,700 | 4P21 --- | 1.40 | 1.86 | 51 | 29 | 73 | 23 |
| 12,700 | 4P21 --- | 1.87 | 2.32 | 51 | 29 | 86 | 23 |

*Manifold at air inlet ends add 1.5-inch (.38mm) to overall length. Manifold cannot support the load weight and must extend beyond the load.

**NOTE ON ESTIMATED AIR FLOW: Air flow listed on this page is an estimate of the air flow at a given load, and a good operating surface. Always multiply this air flow data times 1.75 (1.5 for Gapmaster) to provide a safety factor or when calculating air compressor requirements.



1170 Andover Park West
Tukwila, WA 98188-3909
USA

phone: +1 206.575.3344
fax: +1 206.575.3505
email: info@aerogo.com
www.aerogo.com

QUALITY MANAGEMENT SYSTEM
ISO 9001:2015
CERTIFICATE FM588888



©AeroGo, Inc.
All Rights Reserved
APL2017